

## SUN SPARC ENTERPRISE M5000 SERVER

### MAINFRAME-CLASS RAS AND UNMATCHED INVESTMENT PROTECTION

#### KEY FEATURES

- Optimized for 24x7 mission critical computing and large shared memory applications
- Mainframe class reliability, availability, serviceability (RAS)
- Unmatched investment protection with no forklift upgrades - upgrade individual components, not the whole system
- Mix and match up to eight SPARC64 VI and/or SPARC64 VII/VII+ processors in the same system
- 100% binary compatibility with earlier versions of your applications
- Built-in, no-cost, and flexible virtualization technology
- Ideal consolidation platform with up to four Dynamic Domains and support for thousands of Oracle Solaris Containers
- Accelerates database applications by 2x, cuts transaction times in half with Oracle's Sun Storage F5100 Flash Array

*Oracle's midrange Sun SPARC Enterprise M5000 server delivers leading reliability, flexibility, and binary compatibility in a value-priced server by combining the power of Oracle Solaris operating system with RAS features traditionally found on mainframe-class systems. Built on the latest quad-core SPARC64 VII/VII+ or dual-core SPARC64 VI processor, the Sun SPARC Enterprise M5000 server provides enterprise-class service levels for medium-to-large databases, scientific and engineering applications, and consolidation/virtualization projects.*



The Sun SPARC Enterprise M5000 server delivers main-frame class reliability, availability, and serviceability.

### Protect Your Investment with Mainframe-Class Reliability, Availability, and Serviceability in a Highly Flexible System

Uniquely protect IT investments with the Sun SPARC Enterprise M5000 servers. Sun offers no forklift upgrades and you can mix and match different speeds/generations of SPARC64 processors in existing and new M-series servers. Benefit from Sun's long term SPARC Enterprise road map and "future-proof" investments with the Sun SPARC Enterprise M5000 server. What's more, many mainframe class RAS features come standard in the Sun SPARC Enterprise M5000 server, including automatic recovery with instruction retry, up to 512 GB of

system memory with error-correcting code (ECC) protection and extended ECC support, guaranteed data path integrity, total SRAM and register protection, and configurable memory mirroring. Plus, the disks, power supply, and fans are redundant and hot-swappable, and the I/O cards are hot-swappable as well.

To enhance flexibility, the Sun SPARC Enterprise M5000 server supports up to four Dynamic Domains CPU board-level domains for large, mission-critical workloads that depend on maximum isolation, and single-socket-level domains for finer granularity with high isolation. For additional flexibility, each system can support thousands of Oracle Solaris Containers, which enable a single Oracle Solaris 10 instance to support many isolated execution environments.

### Oracle Solaris: The World's Most Advanced Operating System

Only Sun Oracle legally assures investment protection with Oracle Solaris with 100% binary compatibility for the past 15 years and counting. The Sun SPARC Enterprise M5000 server is preinstalled with Oracle Solaris 10. Oracle Solaris 10 also delivers revolutionary features, including Dynamic Tracing (DTrace), Oracle Solaris ZFS, cryptographic infrastructures, IP filter, and User and Process Rights Management.

### Sun SPARC Enterprise M5000 Server Specifications

Processor	
Up to eight SPARC64 VII/VII+ quad-core processors or eight dual-core SPARC64 VI processors	
SPARC V9 Architecture, ECC protected	
Cache per SPARC64 Level 1	<ul style="list-style-type: none"> <li>• SPARC64 VII+: 64 KB D-cache and 64 KB I-Cache</li> <li>• SPARC64 VII: 64 KB D-cache and 64 KB I-Cache</li> <li>• SPARC64 VI: 128 KB D-cache and 128 KB I-Cache</li> </ul>
Cache per SPARC64 Level 2	<ul style="list-style-type: none"> <li>• SPARC64 VII+: 2.66GHz: 11 MB on-chip</li> <li>• SPARC64 VII 2.53GHz: 5.5 MB on-chip</li> <li>• SPARC64 VI 2.15GHz: 5 MB on-chip</li> </ul>
Clock speed	<ul style="list-style-type: none"> <li>• SPARC64 VII+: 2.66 GHz</li> <li>• SPARC64 VII: 2.53 GHz</li> <li>• SPARC64 VI: 2.15 GHz</li> </ul>
System	
CPU	One to four CPU (CMU), two CPUs per board
Main memory	Up to 512 GB per domain/system, using 8 GB DIMMs (64 GB per memory board x eight boards)
I/O	<ul style="list-style-type: none"> <li>• Up to 10 I/O slots with eight PCIe slots each and two PCI-X (four PCIe and one PCI-X per I/O tray)</li> <li>• Up to 50 PCIe or PCI-X slots with optional External I/O Expansion Unit</li> </ul>
System bus	High-speed, low-latency interconnect system bus with redundant data, address, and response crossbar interconnect
System bus bandwidth (memory)	<ul style="list-style-type: none"> <li>• 64 GB/sec peak, 24.831 GB/sec stream (copy)</li> </ul>
System bus bandwidth (I/O)	<ul style="list-style-type: none"> <li>• 16 GB/sec peak</li> </ul>
Service processor for system management	
Up to four Dynamic Domains	

<b>Storage</b>	
Boot device	<ul style="list-style-type: none"> <li>Up to four internal, 2.5 in. SAS boot disks</li> </ul>
External	<ul style="list-style-type: none"> <li>Direct, SAN or NAS attached to Sun StorageTek compatible tape libraries, flash array, and disk arrays, including StorageTek 3X00, 5X00, 6X00, 9X00, and Jx000 families and Sun Storage F5100 Flash Array</li> </ul>
<b>Resource Management</b>	
Dynamic Domains	
Oracle Solaris 10 Resource Manager including Oracle Solaris Containers	
<b>Software</b>	
Operating system	<ul style="list-style-type: none"> <li>SPARC64 VII+ (2.66GHz): Oracle Solaris 10 (12/07) (Update 4) with Maintenance Update 8 (MU8) or later and XCP 1100</li> <li>SPARC64 VII (2.53GHz): Oracle Solaris 10 (8/07)* or later</li> <li>SPARC64 VI (2.15GHz): Oracle Solaris 10 (11/06) or later</li> </ul> <p>*Oracle Solaris 10 (10/08) or Oracle Solaris 10 (8/07) require Oracle Solaris 10 10/09 Patch Bundle and the Sun Alert Patch Cluster</p>
Languages	C, C++, Pascal, FORTRAN, Java
Networking	ONC/NFS, TCP/IP, SunLink, Netware
System monitoring	<ul style="list-style-type: none"> <li>Sun Management Center</li> <li>Oracle Solaris Web Start</li> <li>Solstice Domain Manager</li> <li>Solstice Enterprise Manager</li> <li>Solstice Backup</li> <li>xVM Ops Center</li> </ul>
Value added software	<ul style="list-style-type: none"> <li>VERITAS File System</li> <li>VERITAS Volume Manager</li> <li>Sun Cluster</li> <li>Sun HPC ClusterTools</li> <li>Sun Java Enterprise System</li> </ul>
<b>Environmental</b>	
AC power	100–240 V AC 1-phase (50/60 Hz), 12 A per power cord, two-to-four power cords
Plug	NEMA-L6-20P (U.S.) or IEC 309-IP44 (INTL) IEC 60320 C19 connector
Receptacle type	IEC 60320 C20
Operating temperature	5°C to 35°C (41°F to 95°F), 20% to 80% relative humidity, noncondensing
Nonoperating temperature	-20°C to 60°C (-4°F to 140°F) 8% to 93% relative humidity, noncondensing
Altitude	Up to 3000 m (9,842 ft.)

### Regulations

Safety	CSA/UL-60950, EN60950, IEC950 CB Scheme with
--------	--

	all national deviations
RFI/EMC	<ul style="list-style-type: none"> <li>• EN55022/CISPR22 Class A</li> <li>• FCC CFR 47 Part 15 Class A</li> <li>• EN61000-3-2</li> <li>• EN61000-3-3</li> </ul>
Immunity	<ul style="list-style-type: none"> <li>• EN55024</li> <li>• EN61000-4-2, -4-3, -4-5, -4-6, -4-8, and -4/11</li> </ul>
Regulatory markings	CE, FCC, ICES, C-Tick, VCCI, GOST-R, BSMI, MIC, CSA/UL
Other marks	WEEE and Chinese RoHS
<b>Key RAS Features</b>	
<ul style="list-style-type: none"> <li>• End-to-end ECC protection</li> <li>• Guaranteed data path integrity</li> <li>• Automatic recovery with instruction retry</li> <li>• Total SRAM and register protection</li> <li>• Dynamic L1 and L2 cache line degradation</li> <li>• ECC and Extended ECC protection for memory, memory mirroring, and Predictive Self-Healing</li> <li>• Fault-isolated Dynamic Domains</li> <li>• Dynamic Reconfiguration</li> <li>• Auto Diagnosis and Recovery</li> <li>• Online Upgrades</li> <li>• Concurrent maintenance of disks, fans, and power supplies</li> <li>• Redundant network connections</li> <li>• Redundant storage connections</li> <li>• Live operating system upgrades</li> <li>• Journaling file system</li> <li>• Hardened I/O drivers</li> <li>• Dynamic individual core or CPU offlining</li> <li>• Memory page retirement</li> <li>• Cluster support</li> </ul>	
<b>Dimensions and Weight</b>	
Height	44.0 cm (17.33 in.)
Width	44.4 cm (17.48 in.)
Depth	81.0 cm (31.9 in.)
Weight	275 lb. (125 kg)

### Warranty

Visit [oracle.com/sun/warranty](http://oracle.com/sun/warranty) for Oracle's global warranty support information on Sun products.

### Services

#### Complete Portfolio of Services from Installation to Operations Management

Oracle Advanced Customer Services offers complete lifecycle management from installation, configuration, management and support for your Sun SPARC Enterprise M5000 servers. Oracle product experts configure, integrate and test your new server technology using Oracle's implementation best practices. To increase the efficiency of your IT team, Oracle services experts offer Oracle Operations Management that provides 24x7 monitoring and management services across the entire IT infrastructure. And, Oracle Premier Support provides the award-winning support you need to maximize the return on your Sun SPARC Enterprise M5000 server investment. From unlimited 24/7 access to Sun system specialists, to critical patches, essential product updates, and exclusive online resources — only Oracle provides integrated support for your entire stack, applications to disk.

Visit [oracle.com/acs](http://oracle.com/acs) for information on Oracle Advanced Customer Services offerings for Oracle server products.

### Contact Us

For more information about Oracle's Sun SPARC Enterprise M5000 server, please visit [oracle.com/sun](http://oracle.com/sun) or call +1.800.786.0404 to speak to an Oracle representative.



Oracle is committed to developing practices and products that help protect the environment

Copyright © 2011, Oracle and/or its affiliates. All rights reserved.

This document is provided for information purposes only and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. UNIX is a registered trademark licensed through X/Open Company, Ltd. 1010

**Hardware and Software, Engineered to Work Together**

